

**Material Safety Data Sheet**

---

**SECTION 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

---

Product Name: PITTWRAP® jacketing

Manufacturer/Supplier:  
Pittsburgh Corning Corporation  
800 Presque Isle Drive  
Pittsburgh, PA 15239

Information Number: 724-327-6100  
CHEMTREC: 800/424-9300

Generic Name: Bitumen resin tape

Use: PITTWRAP® jacketing is a heat sealable multiple laminate, modified bituminous membrane for protecting underground FOAMGLAS® insulation systems.

General Comments: General information and emergency information available 8:00 AM – 5:00 PM Monday through Friday.

CHEMTREC telephone number is to be used only in the event of chemical transportation emergencies involving a spill, leak, fire, exposure, or accident involving chemicals. All non-emergency questions should be directed to technical service.

---

**SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS**

---

<b>Ingredient</b>	<b>App. % by wt.</b>	<b>CAS #</b>
Asphalt	80 -95	8052-42-4
Aromatic Oil	5-15	64742-04-7
Petroleum Resins	<2	64742-16-1

---

**SECTION 3 – HAZARDOUS IDENTIFICATION**

---

HAZARDOUS POLYMERIZATION: Will Not Occur

ROUTES OF EXPOSURE: Inhalation, Skin, Eyes and Ingestion.

IMMEDIATE EFFECTS:

**INHALATION:** Due to the nature of the product, there is no inhalation hazard. Heated vapors may cause irritation of nasal passages and throat.

**SKIN CONTACT:** Normally not irritating. If rash develops or irritation persists, seek physician.

**EYE CONTACT:** If eye contact is made and irritation develops, contact physician.

**INGESTION:** Due to nature of product ingestion is not likely. If ingested, see physician.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

**ACUTE:** Inhalation – exposure during hot process may cause respiratory, eye, or nose irritation.

**CHRONIC:** Inhalation – Long term exposure to concentrated hot processing fumes may reduce lung function and cause chronic bronchitis

**Material Safety Data Sheet**

**SECTION 4 – FIRST AID MEASURES**

GENERAL ADVICE:

- INHALATION:** Due to the nature of the product, there is no inhalation hazard. Heated vapors may cause irritation of nasal passages and throat. If a person breathes large amounts of heated product vapors, move the exposed person to fresh air at once. If breathing difficult, GET MEDICAL ATTENTION.
- SKIN CONTACT:** Normally not irritating. If rash develops or irritation persists, seek physician.
- EYE CONTACT:** Remove contact lenses. Flush eyes with large amounts of water, preferably lukewarm water, for at least 15 minutes. If irritation persists, GET MEDICAL ATTENTION.
- INGESTION:** Due to nature of product ingestion is not likely. If ingested, see physician.

**SECTION 5 – FIRE FIGHTING MEASURES**

- SUITABLE EXTINGUISHING MEDIA:** Foam, Carbon Dioxide or dry chemical. If entering a confined area, use self-contained breathing apparatus if applicable
- EXPLOSION DATA:**
- SENSITIVITY TO MECHANICAL IMPACT:** Stable.
- SENSITIVITY TO STATIC DISCHARGE:** Stable.

**SECTION 6 – ACCIDENTAL RELEASE MEASURES**

- PRECAUTIONS FOR PERSONNEL:** No special clothes are required, but do wear gloves.
- ENVIRONMENTAL PRECAUTIONS:** No special procedures normally needed.
- PROCESS FOR CLEANING:** Absorb with inert material. Remove sources of ignition. Scoop material with non-sparking tools.

**SECTION 7 – HANDLING AND STORAGE**

- HANDLING:** Avoid direct contact with product. No special ventilation required.
- STORAGE:** Store away from ignition sources and open flames.

**SECTION 8 – EXPOSURE RESTRICTIONS AND PERSONAL PROTECTION**

Ingredient	App. % by wt.	EXPOSURE LIMITS			CAS #
		TLV	NIOSH REL TWA	PEL	
Asphalt	80 -95	0.5 mg/m <sup>3*</sup>	0.5 mg/m <sup>3</sup>	NE	8052-42-4
Aromatic Oil	5-15	0.2 mg/m <sup>3*</sup>	0.2 mg/m <sup>3</sup>	0.2 mg/m <sup>3</sup>	64742-04-7
Petroleum Resins	<2	UN	5 mg/m <sup>3</sup>	UN	64742-16-1

\* As Fumes

- ADDITIONAL ADVICE:** No special clothes are required, but do wear gloves.

**SECTION 9 – PHYSICAL PROPERTIES**

**Material Safety Data Sheet**

Freezing Point: °C (°F)	NA	Flash Point : °C (°F) TCC	>316(600)
Boiling Point: °C (°F)	NA	Ignition Temperature: °C (°F)	
Vapor Pressure (MM Hg):	NA	Flammable Limits: LEL	NA
		UEL	NA
Vapor Density (Air = 1)	NA	Specific Gravity (H <sub>2</sub> O = 1):	1.0
Solubility in Water:	Insoluble	Percent Volatile By Volume (%)	Nil
Appearance and Odor:	Black bitumen compound with clear polyester top film. Odor is asphaltic.	pH:	NA
		Evaporation Rate (BuAC=1)	NA

**SECTION 10 – STABILITY AND REACTIVITY**

**STABILITY:** Stable

**CONDITIONS TO AVOID:** Open Flame.

**MATERIALS TO AVOID:** None known

**DECOMPOSITION PRODUCTS:** Carbon Monoxide, Carbon Dioxide and Oxides of Nitrogen.

**EYES:** Remove contact lenses. Flush eyes with large amounts of water, preferably lukewarm water, for at least 15 minutes. If irritation persists, GET MEDICAL ATTENTION.

**SKIN:** If solid product gets on the skin, wash the contaminated skin with soap and water. If irritation develops or persists after the area has been washed, GET MEDICAL ATTENTION. Should molten material strike the skin, flush with cold water. Thoroughly wash exposed area with mineral oil and flush with water. GET MEDICAL ATTENTION.

**INHALATION:** If a person breathes large amounts of heated product vapors, move the exposed person to fresh air at once. If breathing difficult, GET MEDICAL ATTENTION.

**CONSUMPTION:** If swallowed, call physician immediately. Only induce vomiting at the instructions of a physician. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

**SECTION 11 – TOXICOLOGICAL INFORMATION**

CAS #	INGREDIENT	DERMAL LD50	INHALATION LD50	ORAL LD50
8052-42-4	Asphalt	NE	NE	NE
64742-04-7	Aromatic Oil	NE	NE	NE
64742-16-1	Petroleum Resins	> 5000 mg/kg (Rat)	> 4000 mg/kg (Rat)	> 5000 mg/kg (Rat)

CAS #	INGREDIENT	CARCINOGENICITY		TERATOGENICITY	MUTAGENICITY
		ACGIH	IARC		
8052-42-4	Asphalt	NE	NE	NE	NE
64742-04-7	Aromatic Oil	NE	YES	NE	NE
64742-16-1	Petroleum Resins	NE	NE	NE	NE

**Material Safety Data Sheet**

---

**SECTION 12 – ECOLOGICAL INFORMATION**

---

VOLATILE ORGANIC COMPOUNDS: 0 Grams Per Liter (g/l). 0 Pounds Per Gallon (lb/g).

---

**SECTION 13 – DISPOSAL CONSIDERATIONS**

---

DISPOSAL METHOD: Disposal should be made in accordance with Federal, State and Local regulations.

---

**SECTION 14 – TRANSPORT INFORMATION**

---

SHIPPING CLASS: Not Regulated

---

**SECTION 15 – REGULATORY INFORMATION**

---

SARA SECTION 302:

SARA (311,312) HAZARD CLASS:

SARA (313) CHEMICALS: NONE

CERCLA: NA

CPSC CLASSIFICATION:

HMIS: FLAMMABILITY: 0 REACTIVITY: 0 HEALTH: 1

NFPA: FLAMMABILITY: 0 REACTIVITY: 0 HEALTH: 1

WHMIS CLASSIFICATION: CLASS D Division 2B CLASS B Division 2

CALIFORNIA PROPOSITION 65:

- A. This product contains a chemical known to the State of CA to cause birth defects or other reproductive harm.
- B. This product contains a chemical known to the State of CA to cause cancer.
- C. This product contains a chemical known to the State of CA to cause cancer and birth defects or other reproductive harm.

---

**SECTION 16 – OTHER INFORMATION**

---

NA = not applicable      NE = not established      UN = unavailable      CL = Ceiling Limit  
 NEGL = Negligible      PROP. = Proprietary

“THE DATA INCLUDED HEREIN ARE PRESENTED IN ACCORDANCE WITH THE VARIOUS ENVIRONMENT, HEALTH AND SAFETY REGULATIONS. IT IS THE RESPONSIBILITY OF A RECIPIENT OF THIS DATA TO REMAIN CURRENTLY INFORMED ON CHEMICAL HAZARD INFORMATION, TO DESIGN AND UPDATE ITS INFORMED ON CHEMICAL HAZARD INFORMATION, TO DESIGN AND UPDATE ITS OWN PROGRAM AND TO COMPLY WITH ALL NATIONAL, FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS APPLICABLE TO SAFETY, OCCUPATIONAL HEALTH, RIGHT-TO-KNOW AND ENVIRONMENTAL PROTECTION.”

WHILE THE INFORMATION AND RECOMMENDATIONS SET FORTH HEREIN ARE BELIEVED TO BE ACCURATE, PITTSBURGH CORNING CORPORATION MAKES NO WARRANTY WITH RESPECT THERETO, AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

PITTWRAP® and FOAMGLAS® are registered trademarks of Pittsburgh Corning Corporation.