



# Material Safety Data Sheet

The Dow Chemical Company

**Product Name:** STYROFOAM\* 10.00 Inch Pipe Billet Extruded Foam Insulation

**Issue Date:** 06/06/2007

**Print Date:** 07 Jun 2007

The Dow Chemical Company encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

## 1. Product and Company Identification

### Product Name

STYROFOAM\* 10.00 Inch Pipe Billet Extruded Foam Insulation

### COMPANY IDENTIFICATION

The Dow Chemical Company  
2030 Willard H. Dow Center  
Midland, MI 48674  
USA

Customer Information Number: 800-258-2436

### EMERGENCY TELEPHONE NUMBER

**24-Hour Emergency Contact:** 989-636-4400

**Local Emergency Contact:** 989-636-4400

## 2. Hazards Identification

### Emergency Overview

**Color:** Blue

**Physical State:** Board

**Odor:** Odorless

**Hazards of product:**

Toxic fumes may be released in fire situations.

### OSHA Hazard Communication Standard

This product is not a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### Potential Health Effects

**Eye Contact:** Solid or dust may cause irritation or corneal injury due to mechanical action.

Fumes/vapor released during thermal operations such as hot-wire cutting may cause eye irritation.

**Skin Contact:** Essentially nonirritating to skin. Mechanical injury only.

**Skin Absorption:** Skin absorption is unlikely due to physical properties.

\* Indicates a Trademark

**Inhalation:** Dust may cause irritation to upper respiratory tract (nose and throat). Fumes/vapors released during thermal operations such as hot wire cutting may cause respiratory irritation. Concentrations of the blowing agents anticipated incidental to proper handling are expected to be well below those which cause acute inhalation effects and below exposure guidelines.

**Ingestion:** Swallowing is unlikely because of the physical state. Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts. May cause choking or blockage of the digestive tract if swallowed.

**Effects of Repeated Exposure:** Contains component(s) which have been reported to cause effects on the following organs in animals: Liver. Lung. Central nervous system. Dose levels producing these effects were many times higher than any dose levels expected from exposure due to use.

**Birth Defects/Developmental Effects:** Chlorodifluoromethane (HCFC-22) caused birth defects in animals only at doses toxic to the mother. Dose levels producing these effects were many times higher than any dose levels expected from exposure due to use.

### 3. Composition Information

Component	CAS #	Amount
Styrene, polymers	9003-53-6	> 85.0 %
1-Chloro-1,1-difluoroethane	75-68-3	<= 10.0 %
Copolymer mixture	Trade secret	< 5.0 %
Chlorodifluoromethane	75-45-6	< 10.0 %
Talc	14807-96-6	< 5.0 %

Extruded polystyrene foam containing a halogenated flame retardant system.

### 4. First-aid measures

**Eye Contact:** Flush eyes with plenty of water; remove contact lenses after the first 1-2 minutes then continue flushing for several minutes. Only mechanical effects expected. If effects occur, consult a physician, preferably an ophthalmologist.

**Skin Contact:** Wash skin with plenty of water.

**Inhalation:** Move person to fresh air; if effects occur, consult a physician.

**Ingestion:** If swallowed, seek medical attention. May cause gastrointestinal blockage. Do not give laxatives. Do not induce vomiting unless directed to do so by medical personnel.

**Notes to Physician:** No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

### 5. Fire Fighting Measures

**Extinguishing Media:** Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam.

**Fire Fighting Procedures:** Keep people away. Isolate fire and deny unnecessary entry. Soak thoroughly with water to cool and prevent re-ignition. If material is molten, do not apply direct water stream. Use fine water spray or foam. Cool surroundings with water to localize fire zone.

**Special Protective Equipment for Firefighters:** Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

**Unusual Fire and Explosion Hazards:** Mechanical cutting, grinding or sawing can cause formation of dusts. To reduce the potential for dust explosion, do not permit dust to accumulate. This product contains a flame retardant to inhibit accidental ignition from small fire sources. This plastic foam product is combustible and should be protected from flames and other high heat sources. For more information, contact Dow. Dense smoke is produced when product burns.

**Hazardous Combustion Products:** During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. In smoldering or

flaming conditions, carbon monoxide, carbon dioxide and carbon are generated. Combustion products may include and are not limited to: Hydrogen halides. Combustion products may include trace amounts of: Hydrogen bromide. Based on combustion toxicity testing, the effects of combustion from this foam are not more acutely toxic than the effects of combustion from common building materials such as wood.

## 6. Accidental Release Measures

**Steps to be Taken if Material is Released or Spilled:** Contain spilled material if possible. Sweep up. Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

**Personal Precautions:** There are no special required instructions.

**Environmental Precautions:** There are no special required instructions.

## 7. Handling and Storage

### Handling

**General Handling:** Fabrication methods which involve cutting into this product may release the blowing agent(s) remaining in the cells. Provide adequate ventilation to assure localized concentrations in release areas are maintained below the lower flammable limit. This product is combustible and may constitute a fire hazard if improperly used or installed. When installed, this product should be adequately protected as directed by national building regulations or instructions in the specific application brochure. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

### Storage

Minimize sources of ignition, such as static build-up, heat, spark or flame. When large quantities of this product are stored or fabricated, blowing agents may be released. Released blowing agents may thermally decompose to form gases which may accelerate corrosion or rust formation of heaters, boilers, gas fired recirculating air furnaces or heaters, or gas water heaters. Flammable vapors may accumulate in some storage situations. In order to prevent buildup of combustible vapors, do not store large quantities of this product in unventilated spaces.

## 8. Exposure Controls / Personal Protection

### Exposure Limits

Component	List	Type	Value
Chlorodifluoromethane	ACGIH	TWA	1,000 ppm
1-Chloro-1,1-difluoroethane	WEEL	TWA	4,100 mg/m <sup>3</sup> 1,000 ppm

### Personal Protection

**Eye/Face Protection:** Eye protection should not be necessary. For fabrication operations safety glasses are recommended. If there is a potential for exposure to particles which could cause eye discomfort, wear chemical goggles.

**Skin Protection:** No precautions other than clean body-covering clothing should be needed.

**Hand protection:** Use gloves to protect from mechanical injury. Selection of gloves will depend on the task.

**Respiratory Protection:** Atmospheric levels should be maintained below the exposure guideline. When respiratory protection is required for certain operations, including but not limited to saw, router or hot-wire cutting, use an approved air-purifying respirator. The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

**Ingestion:** No precautions necessary due to the physical properties of the material.

### Engineering Controls

**Ventilation:** Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines.

## 9. Physical and Chemical Properties

Physical State	Board
Color	Blue
Odor	Odorless
Flash Point - Closed Cup	Not applicable
Flammable Limits In Air	<b>Lower:</b> Not applicable <b>Upper:</b> Not applicable
Autoignition Temperature	354 °C (669 °F) <i>ASTM D1929</i>
Vapor Pressure	Not applicable
Boiling Point (760 mmHg)	Not applicable.
Vapor Density (air = 1)	Not applicable
Specific Gravity (H2O = 1)	0.027 - 0.064 <i>Estimated</i>
Liquid Density	Not applicable
Freezing Point	Not applicable
Melting Point	90 - 130 °C (194 - 266 °F) <i>Estimated</i>
Solubility in Water (by weight)	insoluble in water
pH	Not applicable
Kinematic Viscosity	Not applicable

## 10. Stability and Reactivity

### Stability/Instability

Thermally stable at typical use temperatures.

**Conditions to Avoid:** Avoid temperatures above 300°C (572°F) Exposure to elevated temperatures can cause product to decompose. Avoid direct sunlight.

**Incompatible Materials:** Avoid contact with oxidizing materials. Avoid contact with: Aldehydes. Amines. Esters. Liquid fuels. Organic solvents.

### Hazardous Polymerization

Will not occur.

### Thermal Decomposition

Does not normally decompose. Evolution of small amounts of hydrogen halides occur when heated over 250°C (482°F). Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Aromatic compounds. Aldehydes. Ethylbenzene. Hydrogen halides. Polymer fragments. Styrene. Under high heat, non-flaming conditions, small amounts of aromatic hydrocarbons such as styrene and ethylbenzene are generated.

## 11. Toxicological Information

### Repeated Dose Toxicity

Contains component(s) which have been reported to cause effects on the following organs in animals: Liver. Lung. Central nervous system. Dose levels producing these effects were many times higher than any dose levels expected from exposure due to use. Additives are encapsulated in the product and are not expected to be released under normal processing conditions or foreseeable emergency.

### Developmental Toxicity

Chlorodifluoromethane (HCFC-22) caused birth defects in animals only at doses toxic to the mother. Dose levels producing these effects were many times higher than any dose levels expected from exposure due to use.

## 12. Ecological Information

### CHEMICAL FATE

#### **Movement & Partitioning**

No bioconcentration is expected because of the relatively high molecular weight (MW greater than 1000). In the terrestrial environment, material is expected to remain in the soil. In the aquatic environment, material is expected to float.

#### **Persistence and Degradability**

Surface photodegradation is expected with exposure to sunlight. No appreciable biodegradation is expected. Most of the chlorodifluoromethane (HCFC-22) diffuses out of the foam in the first years of the product's life, most of it degrading in the troposphere to CO<sub>2</sub>, HCl, and HF. Chlorodifluoromethane (HCFC 22) has a stratospheric ozone depletion potential (ODP) of 0.055, relative to CFC 12 (ODP=1). Chlorodifluoroethane (HCFC-142b) remains in the foam and diffuses out slowly, most of it degrading in the troposphere to CO<sub>2</sub>, HCl, and HF. Chlorodifluoroethane (HCFC 142b) has a stratospheric ozone depletion potential (ODP) of 0.065, relative to CFC 12 (ODP=1).

### ECOTOXICITY

Not expected to be acutely toxic to aquatic organisms.

## 13. Disposal Considerations

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. DOW HAS NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Landfill. Incinerator or other thermal destruction device. As a service to its customers, Dow can provide names of information resources to help identify waste management companies and other facilities which recycle, reprocess or manage chemicals or plastics, and that manage used drums. Telephone Dow's Customer Information Group at 1-800-258-2436 or 1-989-832-1556 (U.S.), or 1-800-331-6451 (Canada) for further details.

## 14. Transport Information

**DOT Non-Bulk**  
NOT REGULATED

**DOT Bulk**  
NOT REGULATED

**IMDG**  
NOT REGULATED

**ICAO/IATA**  
NOT REGULATED

*This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.*

## 15. Regulatory Information

### OSHA Hazard Communication Standard

This product is not a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Immediate (Acute) Health Hazard	No
Delayed (Chronic) Health Hazard	No
Fire Hazard	No
Reactive Hazard	No
Sudden Release of Pressure Hazard	No

### Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This product contains the following substances which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and which are listed in 40 CFR 372.

Component	CAS #	Amount
Chlorodifluoromethane	75-45-6	< 10.0 %
1-Chloro-1,1-difluoroethane	75-68-3	<= 10.0 %

### Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Hazardous Substances List and/or Pennsylvania Environmental Hazardous Substance List:

The following product components are cited in the Pennsylvania Hazardous Substance List and/or the Pennsylvania Environmental Substance List, and are present at levels which require reporting.

Component	CAS #	Amount
Talc	14807-96-6	< 5.0 %
Chlorodifluoromethane	75-45-6	< 10.0 %
1-Chloro-1,1-difluoroethane	75-68-3	<= 10.0 %

### Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Special Hazardous Substances List:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

### California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

### US. Toxic Substances Control Act

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

### CEPA - Domestic Substances List (DSL)

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

## 16. Other Information

### Hazard Rating System

NFPA	Health	Fire	Reactivity
	0	1	0

### Recommended Uses and Restrictions

Thermal insulation. For industrial use. Dow recommends that you use this product in a manner consistent with the listed use. If your intended use is not consistent with Dow's stated use, please contact Dow's Customer Information Group.

### Revision

Identification Number: 81721 / 0000 / Issue Date 06/06/2007 / Version: 2.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

### Legend

N/A	Not available
W/W	Weight/Weight
OEL	Occupational Exposure Limit
STEL	Short Term Exposure Limit
TWA	Time Weighted Average
ACGIH	American Conference of Governmental Industrial Hygienists, Inc.
DOW IHG	Dow Industrial Hygiene Guideline
WEEL	Workplace Environmental Exposure Level
HAZ_DES	Hazard Designation
Action Level	A value set by OSHA that is lower than the PEL which will trigger the need for activities such as exposure monitoring and medical surveillance if exceeded.

*The Dow Chemical Company urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.*