

CLEANER



RG-2400[®] Cleaner is a low V.O.C., fast-acting, readily biodegradable cleaner which lifts heavy grease, oil, synthetic oil, and preservatives. Cleans accumulated cutting fluids and petroleum residues. Developed to remove and clean up the **RG-2400[®] Cleaner** corrosion gels. Biodegradable, non-petroleum, high flash point, low V.O.C., maximum strength formulation is ready-to-use. Clean up any residue with soap and water.

<u>TEST METHOD</u>	<u>DESCRIPTION</u>	<u>RESULTS</u>
ASTM E-659	Auto ignition Temperature	253°C
	Ignition Delay Time	136.5 seconds
	Barometric Pressure	757 mm Hg
ASTM D-92	Flash Point & Fire Point	245°F*
	*occurred simultaneously	
ASTM D-93	Flash Point	184°F
ASTM D-1218	Refractive Index	1.45775 @ 25°C
ASTM D-1120	Boiling Point	528°F @ 761 mm Hg
ASTM D-1177	Freezing Point	No Distinct Inflections
ASTM D-2879	Vapor Pressure @ 25°C	1.8 mm Hg
ASTM D-1298	Specific Gravity	29.2 @ 60°F

Ingredients are E.P.A. listed as approved replacement chemical for solvent usage.

DISPOSE OF CLEANING RESIDUES IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAWS AND REGULATIONS.

**RG FAMILY OF PRODUCTS ARE PROTECTED BY NUMEROUS U.S. AND INTERNATIONAL PATENTS
- OTHER PATENTS PENDING-**

Polyguard

WWW.RG2400.COM